

jayafurring™

Concealed Grid




Cocok Untuk

- Ruang server/data
- Industrial
- Mall
- Gedung peribadatan
- Auditorium Hall

Komponen Sistem

Komponen Utama



200, 201, 202

Primary Section (3600 mm)
 PN 200 30 mm Top Cross Rail 0.4 mm (BMT)
 PN 201 30 mm Top Cross Rail 0.5 mm (BMT)
 PN 202 30 mm Top Cross Rail 0.7 mm (BMT)



204, 205

Secondary Section (4800 mm)
 PN 204 23 mm Furring Channel 0.4mm (BMT)
 PN 205 23 mm Furring Channel 0.5mm (BMT)



210N

Primary & Secondary Connectors
 PN 210N Furring Channel to Top Cross Rail



212EX

Perimeter Sections (3000 mm)
 PN 212EX 19 x 19 Wall Angle 0.4 mm (TCT)

Aksesoris



219

Direct Fixed Clips

PN 219 Furring Channel to Concrete/Masonry



220N

221

Suspension Bracket

PN 220N Suspension Rod to Concrete
 PN 221 Suspension Rod to Timber/Steel



223SS

224SS

Suspension Clip

PN 223SS Top Cross Rail Spring Adjusted 4 mm Rod
 PN 224SS Top Cross Rail Spring Adjusted 5 mm Rod

Suspension Rods & Nuts

PN 225 4 mm Soft Galvanised Suspension Rod (3600 mm)
 PN 226 5 mm Soft Galvanised Suspension Rod (3600 mm)



Safety Factor
 min 3X



Bersertifikat
Tahan Api
 (hingga 2 jam)*






Luas Area Plafon
 >100m²



Performa
Heavy Load Duty

*)Syarat & ketentuan berlaku

Aksesoris



jayaboard®
 Kini dan seterusnya

jayaboard.com

PLASTERBOARD

CEILINGS

INTERIOR FINISHES

METAL FRAMING

SUBSTRATES

Hotline : (021) 797 7777 WhatsApp : 08118120205

[Jayaboard.id](https://www.facebook.com/Jayaboard.id)

[Jayaboardtube](https://www.youtube.com/Jayaboardtube)

[Jayaboard.id](https://www.instagram.com/Jayaboard.id)

[@jayaboardtwit](https://twitter.com/jayaboardtwit)



jayafurringTM



PRODUCT DATA SHEET

1. Karakteristik Rangka


- *Steel Grade* : G300
- *Yield Strength* : Mpa-300min, 340-400 (typical)
- *Tensile Strength* : Mpa-340min, 360-480 (typical)
- *Coating Class* : AZ-50 or Z180*
- *Ketebalan* : Sesuai Spesifikasi

2. Informasi pada Rangka : Kode Produksi, ketebalan x lebar x panjang

3. Dimensi Rangka :

Top Cross Rail	Furring Channel
 Kode Produk : PN 200, PN 201, PN 202 Ketebalan : 0,4mm BMT 0,5mm BMT 0,7mm BMT	 Kode Produk : PN 204, PN 205 Ketebalan : 0,4mm BMT 0,5mm BMT

4. Aksesoris :

Suspension Clip Adjuster	Connector	Suspension Rod
 Kode Produk : - PN 223SS Top cross rail adjuster for 4mm - PN 224SS Top cross rail adjuster for 5mm	 Kode Produk : PN 210N Furring channel to top cross rail connector	 Kode Produk : - PN 225 Ø 4mm soft galvanized suspension rod - PN 226 Ø 5mm soft galvanized suspension rod

- * - AZ-50 : Zinc-Iron Alloy Coated, ketebalan ± 50 gr/m²
- Z180 : Zinc Coated, ketebalan 150-180 gr/m²

Bahan baku sesuai **SNI**
Pemasangan sistem sesuai dengan ASTM C840

